



# SBM 655

Full Featured, High Volume  
Video Wheel Balancer

From Unbalanced To 0.00's  
in **ONE SPIN**



Graphics Display Proper  
Procedures

3 Dimension Automatic  
Entry With Stick On  
Weight Applicator

Hidden Weight Spoke Mode

Foot Brake For Precise  
Weight Placement

Quick Nut Standard

Long 40mm Shaft  
Accommodates Flange  
Plates, Motorcycle Wheels  
And Wide Wheel Assemblies

Engineered For High  
Volume Tire Shops

**Designed For  
Alloy Wheels**

SEE VIDEO DEMONSTRATIONS AT  
WWW.GRPEQUIP.COM



Precision Stick On Weight Placement With ALU Data Arm



Easy To Read Graphics Display Guides Technician Through All Processes



### Optional Accessories



606200

Open Center Offset Spacer  
Allows Back Coning Of  
Truck And SUV Wheels For  
An Accurate Balance



606300

Two Sided Truck Cone  
For Light/Medium Trucks  
And SUV's

Voltage	Max Wheel Weight	Max Tire Diameter	Onboard Adaptor Storage	Max Rim Width	Max Rim Diameter	Max Rim Diameter For Weight Applicator
110 Volt	150 Lbs.	44"	7	20"	30"	26"

\* 4 Cone Set Standard

**GRP Enterprises LLC.**  
PO Box 6700  
11011 Leadbetter Rd.  
Ashland, VA 23005  
(804) 365-7959 FAX (772)402-4548  
www.grpequip.com

